




HISENSE AIR CONDITIONER 12000BTU R32 INVERTER

Model No: HNABAC12TR4RYRCA05OD



Price:

Rs. 254,990

Warranty:

0 (s) manufacturer warranty.

Delivery:

Delivery - Standard 7 Days.

- Delivery Within 7 **Days**.
- For Any Invoice Above Rs.10,000, Free Islandwide Delivery Available.
- For Any Invoice Below Rs.10,000, A Delivery Rate Of Rs.300 Will Be Charged.

Specifications:

- Model: AS-12TR4RYRCA00
- Type: T1, CO, Inverter
- Cooling Capacity: Btu/h 12283
- Heating Capacity: W /
- Rated Input-Cooling: W 1160
- Rated Input-Heating: W /
- Moisture Removal: L/H.r /
- Air Circulation (Indoor): m3/h 550
- Air Circulation (Outdoor): m3/h /
- CSPF for Cooling: W/W 4.6
- SCOP for Heating: W/W /
- Energy Class: Heatling /
- Refrigerant: R32
- Refrigerant charge volume: g
- : 500
- Indoor Unit Noise Level - High: High(dB (A)) - 38
- Indoor Unit Noise Level - Low: Low(dB (A)) - 32
- Outdoor Unit Noise Level: dB(A): 49
- Voltage, Frequency, Phase: 220-240V~,50Hz,1P
- Rated Current: Cooling (A): 5
- Rated Current: Heating (A): /
- Degree of protection (IN) / (O: (IP) IPX0/IPX4
- Class of electroprotection (IN: (I/II) CLASS I / CLASS I
- maximal pipe length: m 25
- maximal heights' interval: m 10
- LRA: A
- Compressor: Type: Rotary
- Compressor: Model No.: KSK89D59UEZC
- Compressor: MFG: GMCC
- Compressor: Expansion Device: Capillary
- Liquid Pipe inch(mm): (1/4)
- Gas Pipe inch(mm): (3/8)
- Display on Front Panel: LED
- LCD Wireless Remote Controller: Yes
- Removable and washable Panel: Yes
- Washable PP Filter: Yes
- 24 Hours Timer: Yes
- 3 Speed and Auto Indoor Fan Control: Yes
- Vertical Auto Swing Louver: Yes
- Horizontal Auto Swing Louver: 1/4^Optional 1/4%: 1/4^Optional 1/4%
- Sleep Operation: Yes
- Smart Function: Yes
- Super Function: Yes
- Compressor Indicator: No

- Auto Restart: Yes
- Dimmer: Yes
- 2 Ways Draining Connection (Left or Right): Yes
- Net Dimensions WxHxD (mm):Indoor Unit: 790x255x200
- Net Dimensions WxHxD (mm):Outdoor Unit: 660Ã—482Ã—240
- Net Weight (Kg):Indoor Unit: 7.3
- Net Weight (Kg):Outdoor Unit: 22.5
- Packing Dimensions WxHxD (mm):Indoor Unit: 850x320x260
- Packing Dimensions WxHxD (mm):Outdoor Unit: 780Ã—530Ã—315
- Gross Weight (Kg):Indoor Unit: 8.5
- Gross Weight (Kg):Outdoor Unit: 25
- Loading Capacity (20'/40'/40'HC))i¼^No pipei¼%o: 158/316/348
- Loading Capacity (20'/40'/40'HC))i¼^With pipei¼%o: 140/280/324
- Test Standard: EN 14511

Date: 2025-10-08 07:38